



## shinken-receiver

### Usage:

shinken-receiver [options]

### Options:

Name	Description
--version	Show program's version number and exit.
-h, --help	Show this help message and exit.
-c INI-CONFIG-FILE, --config=INI-CONFIG-FILE	Config file.
-d, --daemon	Run in daemon mode.
-r, --replace	Replace previous running receiver.
--debugfile=DEBUG_FILE	Debug file. Default: not used (why debug a bug free program? :)).

## shinken-arbiter

### Usage:

shinken-arbiter [options] -c configfile [-c additional\_config\_file]

### Options:

Name	Description
--version	Show program's version number and exit.
-h, --help	Show this help message and exit.
-c CONFIG-FILE, --config=CONFIG-FILE	Config file (your <i>nagios.cfg</i> ). Multiple -c can be used, it will be like if all files was just one.
-d, --daemon	Run in daemon mode.
-r, --replace	Replace previous running arbiter
--debugfile=DEBUG_FILE	Debug file. Default: not used (why debug a bug free program? :)).
-v, --verify-config	Verify config file and exit.
-p PROFILE, --profile=PROFILE	Dump a profile file. Need the python cProfile library
-a ANALYSE, --analyse=ANALYSE	Dump an analyse statistics file, for support.
-m MIGRATE, --migrate=MIGRATE	Migrate the raw configuration read from the arbiter to another module. <b>VERY EXPERIMENTAL!</b>
-n ARB_NAME, --name=ARB_NAME	Give the arbiter name to use. <b>Optional</b> , will use the host address if not provide to find it.

## shinken-poller

### Usage:

shinken-poller [options]

### Options:

Name	Description
--version	Show program's version number and exit.
-h, --help	Show this help message and exit.
-c INI-CONFIG-FILE, --config=INI-CONFIG-FILE	Config file.
-d, --daemon	Run in daemon mode.
-r, --replace	Replace previous running poller.
--debugfile=DEBUG_FILE	Debug file. Default: not used (why debug a bug free program? :).
-p PROFILE, --profile=PROFILE	Dump a profile file. Need the python cProfile library.

## shinken-scheduler

### Usage:

shinken-scheduler [options]

### Options:

Name	Description
--version	Show program's version number and exit.
-h, --help	Show this help message and exit.
-c INI-CONFIG-FILE, --config=INI-CONFIG-FILE	Config file.
-d, --daemon	Run in daemon mode.
-r, --replace	Replace previous running scheduler.
--debugfile=DEBUG_FILE	Debug file. Default: not used (why debug a bug free program? :).
-p PROFILE, --profile=PROFILE	Dump a profile file. Need the python cProfile library.

## shinken-broker

### Usage:

shinken-broker [options]

**Options:**

Name	Description
--version	Show program's version number and exit.
-h, --help	Show this help message and exit.
-c INI-CONFIG-FILE, --config=INI-CONFIG-FILE	Config file.
-d, --daemon	Run in daemon mode.
-r, --replace	Replace previous running broker.
--debugfile=DEBUG_FILE	Debug file. Default: not used (why debug a bug free program? :).
-p PROFILE, --profile=PROFILE	Dump a profile file. Need the python cProfile library.

## shinken-reactionner

**Usage:**

shinken-reactionner [options]

**Options:**

Name	Description
--version	Show program's version number and exit.
-h, --help	Show this help message and exit.
-c INI-CONFIG-FILE, --config=INI-CONFIG-FILE	Config file.
-d, --daemon	Run in daemon mode.
-r, --replace	Replace previous running reactionner.
--debugfile=DEBUG_FILE	Debug file. Default: not used (why debug a bug free program? :).
-p PROFILE, --profile=PROFILE	Dump a profile file. Need the python cProfile library.

## shinken-synchronizer

**Usage:**

shinken-synchronizer [options] -c configfile [-c additional\_config\_file]

**Options:**

Name	Description
--version	Show program's version number and exit.

-h, --help	Show this help message and exit.
-c CONFIG-FILE, --config=CONFIG-FILE	Config file (your nagios.cfg). Multiple -c can be used, it will be like if all files was just one.
-d, --daemon	Run in daemon mode.
-r, --replace	Replace previous running arbiter.
--debugfile=DEBUG_FILE	Debug file. Default: not used (why debug a bug free program? : ) ).
-v, --verify-config	Verify config file and exit.