

Daemons listing/enable/disable

shinken-daemons-list

This tool is used to list the daemons configured on your local server.

note: this tool must be launched as **root**.

Usage:

```
shinken-daemons-list
```

Options:

Name	Description
--version	Show program's version number and exit.
-h, --help	Show this help message and exit.

Sample Output

```
$ shinken-daemons-list

arbiter           : DISABLED
broker            : DISABLED
central           : DISABLED
poller            : DISABLED
reactionner       : DISABLED
receiver          : ENABLED
scheduler         : DISABLED
synchronizer      : ENABLED
```

shinken-daemons-enable

This tool is used to enable a daemon on your local server

note: this tool must be launched as **root**.

Usage:

```
shinken-daemons-enable [arbiter poller synchronizer scheduler reactionner receiver broker]
```

Options:

Name	Description
------	-------------

--version	Show program's version number and exit.
-h, --help	Show this help message and exit.

Sample Output

```
$ shinken-daemons-enable reactionner poller
reactionner      : ENABLED
poller           : ENABLED
```

shinken-daemons-disable

This tool is used to disable a daemon on your local server

note: this tool must be launched as **root**.

Usage:

```
shinken-daemons-disable [arbiter poller synchronizer scheduler reactionner receiver broker]
```

Options:

Name	Description
--version	Show program's version number and exit.
-h, --help	Show this help message and exit.

Sample Output

```
$ shinken-daemons-disable reactionner poller
reactionner      : DISABLED
poller           : DISABLED
```